

IEEE Standards Interpretation for IEEE Std 1003.1™-1990 IEEE Standard for Information Technology--Portable Operating System Interfaces (POSIX®)

Copyright © 2001 by the Institute of Electrical and Electronics Engineers, Inc. 3 Park Avenue New York, New York 10016-5997 USA All Rights Reserved.

Interpretations are issued to explain and clarify the intent of a standard and do not constitute an alteration to the original standard. In addition, interpretations are not intended to supply consulting information. Permission is hereby granted to download and print one copy of this document. Individuals seeking permission to reproduce and/or distribute this document in its entirety or portions of this document must contact the IEEE Standards Department for the appropriate license. Use of the information contained in this document is at your own risk.

IEEE Standards Department Copyrights and Permissions 445 Hoes Lane, Piscataway, New Jersey 08855-1331, USA

Interpretation Request #103

Topic: posix_spawn **Relevant Sections:** 3.1.6 PASC

1003.1d, Section 3.1.6.2 (d14,p22,l368-370) omits to say when the change of default signal behavior takes place.

Add to step 2, after signal mask, "signal default actions"

Interpretation Response

The standard does not speak to this issue, and as such no conformance distinction can be made between alternative implementations based on this. This is being referred to the sponsor.

Rationale for Interpretation

This appears to be an omission.

Notes to Project Editor (not part of this interpretation)

The 1003.1 revision should accept the solution proposed in section 11 above. Forwarded to Interpretations group: 21 May 2000 Proposed resolution: 28 May 2000 Finalized Interpretation: 25 July 2000